

### A detailed study of carbon chemical erosion in L-mode plasmas in the DIII-D divertor



#### D. G. Whyte, University of Madison - Wisconsin

J.N. Brooks, *Argonne National Laboratory*P.C. Stangeby, *University of Toronto*N.H. Brooks, *General Atomics* 

Plasma-Facing Components Meeting
May 3, 2004
University of Illinois



#### **Outline**





- L-mode plasmas for carbon erosion studies
- Erosion modeling and interpretation
- Erosion with attached divertor plasma
  - > Divertor tile vs. main-wall tile
  - ➤ Determination of Y<sub>chem</sub> at outer strikepoint
  - > Atomic carbon velocity distribution
- Effect of plasma detachment on carbon erosion.
- Discussion & Summary



### H-mode plasma studies showed unexpected reduction in carbon erosion in the DIII-D divertor









- Encouraging results on the use of carbon:
  - ➤ In-situ Y<sub>chem</sub> reduction at lower divertor.
  - Detachment, necessary for heat flux control, greatly reduces HC signals
- ...but *tentative* results:
  - Inconsistent plasma conditions over long-term study
  - ELMs in H-mode complicate interpretation of erosion and spectroscopy.



### L-mode, simple-as-possible plasmas ideal for carbon studies








- Low power leads to  $\sim$  constant  $T_{surf} \sim 375 \text{ K}$
- No ELMs
- Density control leads to good detachment control
- Multiple discharges
  - ➤ Improved DTS statistics
  - Redundant divertor diagnosis
  - Multiple C & HC emissions measured.




# High resolution spectroscopy and divertor sweeping diagnose erosion over wide variety of surfaces





- Absolute wavelength calibration from discharge lamps during plasma shot (+/- 0.001 nm ~ 300 m/s).
- Can resolve  $T_C < 0.5$  eV.



- Divertor tiles made from ATJ graphite, an isostatically molded fine grain graphite
- Multiple (>50) boronization layers applied over +10 year lifetime.




## WBC Monte-Carlo code is used to interpret HC spectroscopy



- Full dissociation chains of methane & higher order HC's
- MOLDYN reflections vs. E
- Full HC spectrum launched into OSP plasma (DTS) with sonic flow to plate.
- Particle followed until redeposition or leave simulation zone (~5-10 cm)
- Added C<sub>2</sub> and C<sub>3</sub> rates for C<sub>2</sub> spectroscopic interpretation.
  - Close to C for ionization & diss. CX negligible in H plasma
- Excitation rates of CD,  $C_2$ , C I and CII vs.  $T_{e,n_e}$  to calculate expected emission --> photon efficiency.

43.5% CD<sub>4</sub>, 3.7% C<sub>2</sub>D<sub>2</sub>, 24.8% C<sub>2</sub>D<sub>4</sub>, 11% C<sub>2</sub>D<sub>6</sub>, 16% C<sub>3</sub>D<sub>6</sub>




CI photon efficiency

$$\left(\frac{XB}{S}\right)_{CI.910nm} = \sum_{i} n_e X_{CI.910nm} (T_e) \Delta t_{i,CI}$$



### Atomic carbon velocity distribution can be an indicator of erosion source





- WBC computes emission weighted f(v<sub>z</sub>) arising from HC dissociation into C I.
- Thompson model with lightion energy cutoff/correction predicts direct CI f(v<sub>z</sub>) from D+ on C physical sputtering.


$$\frac{df_{\nu}(E)}{d\nu} \propto \left(\frac{E^{3/2}}{(E+E_B)^3}\right) \left(1 - \left(\frac{E_B+E}{\gamma(1-\gamma)E}\right)^{1/2}\right)$$


$$\gamma = \frac{4m_C m_D}{\left(m_C + m_D\right)^2} \sim 0.49$$



### The main/inner wall tiles has 5-6 times higher $Y_{chem}$ than the inner divertor tiles







- V1 is a rare location for ISP, small particle/energy fluence.
- Spectroscopy verifies
   ~identical ISP plasmas at two locations:


$$T_e \sim 10 \text{ eV}$$
  
 $n_e \sim 1.5 \times 10^{19} \text{ m}^{-3}$ 

 Boron (BD) higher from inner wall.



# Attached outer strikepoint is dominated by physical sputtering, $Y_{chem}$ = 0.3%






- Incident plasma:  $T_e=20 \text{ eV}$ ,  $E_i \sim 5 \text{ T}=100 \text{ eV}$ ,  $n_e \sim 2.5 \times 10^{19} \text{ m}^{-3}$
- Matches of CD/C<sub>2</sub> ratio gives confidence in HC modeling.
- Match of CII/CI ratio gives confidence in ion transport modeling.



# Neither erosion model fits the CI spectral features.





- Calculated f(v<sub>z</sub>) convoluted with spectrometer instrumental function for comparison to measured CI spectra.
- Discrepancy with sputtering models unresolved.
  - $\triangleright$  Physical:  $T_{eff} \sim 1$  eV OK, shift too large
  - ightharpoonup Chemical WBC: shift OK, but  $T_{eff}$ ~3 eV too large.
- N.B. chemical erosion can actually lead to higher  $T_{\rm eff,CI}$  than physical sputtering



# WBC modeling predicts increasing photon efficiency in detached plasmas



CASE	WBC-20	WBC-21	WBC-22
Plasma parameters at outer strikepoint			
Te (eV)	20	5	1
$n_e (m^{-3})$	2.5e19	1.05e20	5.6e20
Photon-emission excitation rate coefficients (m <sup>3</sup> /s)			
C I (910 nm)	1.7e-15	1.5e-17	5.e-19
CD (431 nm)	5.6e-15	7e-15	1.5e-15
$C_2$ (516 nm)	2e-14	4e-14	1.16e-14
$C^{+}$ (514 nm)	5e-16	nil	nil
Photon efficiencies: Full hydrocarbon spectrum launched			
CI	4.4e-03	1.6e-3	1.7e-3
CD	5.1e-2	0.45	0.22
$C_2$	1.1e-2	0.83	9.8
CII	4.2e-3		


- C<sub>2</sub> is particularly interesting case:
  - in 1 eV plasma no e- impact ionization /dissociation but readily excited by e- impact  $(E_{th}\sim 2.4 \text{ eV})$ .
- In qualitative agreement with  $C_2D_4$  injection on JET at high density... $C_2$  most easily excited (Stamp et al.)

PFC meeting, May 2004, Whyte




### Detachment strongly suppresses signatures of chemical erosion at the OSP






 HC brightness decreases to or below detection limits (open symbols) in detachment.





### Detachment strongly suppresses signatures of chemical erosion at the OSP





• HC brightness decreases to or below detection limits (open symbols) in detachment.

#### • BD behavior significant:


- Must radiate in detached plasma(MFP ~1 mm)
- $\triangleright$  Verifies  $T_e \sim 1$  eV to sustain BD emission.
- ➤ Ultra-low  $T_e$  cannot be cause of extinction of HC emission, since  $E_{th} \sim$  identical between BD & CD.

PFC meeting, May 2004, Whyte



### Detachment strongly suppresses signatures of chemical erosion at the OSP: $Y_{chem} \le 10^{-4}$









#### **ISP** behaves nearly identical to **OSP**:



#### No apparent difference between locations in Y<sub>chem</sub>

- Implies Y  $_{chem}$  ~0.3% in attached case.
  - ➤ No DTS for modeling.
- No difference between net erosion dominated OSP (stars) and sooty, redeposited ISP tiles.







#### **ISP** behaves nearly identical to **OSP**:




#### No apparent difference between locations in Y<sub>chem</sub>

- Implies Y<sub>chem</sub> ~0.3% in attached case.
  - ➤ No DTS for modeling.
- No difference between net erosion dominated OSP (stars) and sooty, redeposited ISP tiles.

#### **FURTHER OBSERVATIONS**

- BD presence: T<sub>e</sub> can support HC emission.
- Lack of HC emission --> little chemical erosion in detached ISP.
- In stark contrast to the divertor, main-wall chemical erosion increases with ~ constant yield.







## Divertor atomic carbon response to detachment varies greatly from HC



- CI brightness is ~
   proportional to ion flux.
- Change in Zeeman splitting indicates CI emitted from ionization front.








# Divertor atomic carbon response to detachment varies greatly from HC



- CI brightness is ~
   proportional to ion flux.
- Change in Zeeman splitting indicates CI emitted from ionization front.
- Little or no change in T<sub>eff</sub>, contradictory to chemical erosion.
- Doppler shift remains inconsistent with physical sputtering.





#### Discussion on dependence of location for



#### $\mathbf{Y}_{\mathsf{chem}}$

- Redeposited layers, e.g inner divertor do **not** have higher chemical erosion.
  - ➤ No difference between ISP & OSP, regions yet dominated by net erosion &deposition respectively.
  - ➤ At strikepoints, almost all C atoms/HC eroded are from a deposited film, since prompt redeposition on ~90%.
- Results indicate **against** importance of boron in reduction.
  - ➤ Slighter higher Y<sub>chem</sub> after boronization
  - ➤ Upper inner wall and main-wall, strong boron presence with no apparent reduction
- Large energy / particle fluence in divertor remains as the "cause" in the relative reduction.



### Discussion on the (near) extinction of HC emission in detachment.



- Accuracy of yield < 10<sup>-4</sup> unknown, but the general results of WBC follow from simple examination
  - The HC dissociation chain is simplified by the lack of ionizing event,  $\rightarrow$  the HC should produce  $C_2$  &/or CD
  - $\triangleright$  BD shows  $C_2$  and CD should radiate efficiently.
- The absence of  $C_2$  &/or CD argues strongly **against**:
  - **1.** The importance of chemical erosion as a carbon source for the plasma (*does not produce C ions*) and
  - **2.** A large role for chemical erosion in determining net erosion / deposition (*MFP of HC molecules < mm << MFP CI, CII*).



# In summary we have verified and further quantified previous H-mode results of carbon erosion, with some new obervations



- Chemical erosion is weak in the DIII-D lower divertor,  $Y_{chem} \sim 0.3 \%$  with attached plasma.
- Same shot comparison indicates that the divertor tiles have less chemical erosion than main, inner wall.
  - ➤ Boron does not appear to be cause of reduction.
- Detachment eliminates the spectroscopic signature of chemical erosion, with a inferred yield through modeling < 10<sup>-4</sup>.